

**NEW FROM DBI/SALA**

**ISO 9001**



# Rope Grab

Hands-Free Mobile Type - Use on 5/8" Rope



*User  
friendly  
design  
eliminates  
nuisance  
lock-ups !*

*Patented*

Finally, a rope grab that is truly "mobile," working just as good on swelled and worn rope as on new!

- Mobile design with hands-free operation automatically follows the user providing maximum freedom of movement.
- Utilizes both inertia and cam locking systems for added safety and to prevent "panic-grab" situations.
- Energy absorbing design reduces the forces generated upon a worker in the event of a fall.
- Detachable design allows the user to attach or remove the device anywhere along the 5/8" lifeline for greater flexibility.
- Durable but lightweight stainless steel and thermoplastic construction stands up to the harshest environments.

**Hook-Up with  
Confidence !**



**EZ-STOP® II  
Shock Absorbing  
Lanyard (1220007)**



**Rope Lifeline 30 ft.  
(1202754)**

**ISO 9001**

**USA**  
3965 Pepin Avenue  
Red Wing, MN 55066  
800-328-6146  
Fax: 651-388-5065  
[www.salagroup.com](http://www.salagroup.com)

**CANADA**  
260 Export Boulevard  
Mississauga, Ontario  
L5S 1Y9  
800-387-7484  
Fax: 905-795-8777  
[www.salagroup.com](http://www.salagroup.com)



# Rope Grab

**Hands-Free Mobile Type for use on 5/8" Rope**



**Compact  
and  
easy to  
use, the  
workers  
clear  
choice!**

**Easy Installation** Simply remove the detent pin, open the hinge and place the rope grab on the 5/8" lifeline. Then, insert the detent pin back in and connect your 3 ft. EZ-STOP® II Shock Absorbing Lanyard to the Rope Grab and to the back D-ring of your harness. The rope grab incorporates a "gravity-latch" mechanism preventing the device from being installed upside-down.

**Easy to Use** Once the system is installed, the rope grab will travel freely up and down the lifeline hands-free eliminating manual repositioning. The worker is safely protected along the entire length of vertical lifeline. The inertia and cam locking systems are much safer than single locking systems. The shock absorbing design also results in lower arresting forces on the worker in the event of a fall.



**Easy to Remove, Relocate, Handle and Store** The rope grab can be attached or removed at any point on the lifeline making it very convenient and easy to use. Simply remove pin, open hinge and remove from lifeline for relocation or storage.

**Versatile & Economical** This lightweight system is reusable and transportable from one job site to another. The revolutionary design enables it to be used on worn or new rope without any of those nuisance lock-ups. Complete with compatible connection point for your lanyard reducing the chance of roll-out.

• **Rope Grab and Kits:**

- 5000335 - Rope Grab for use on 5/8" lifeline
- 5002042 - Rope Grab with attached 3 ft. EZ-STOP® Shock Absorbing Lanyard
- 5000400 - Rope Grab System; 5000335 Rope Grab, 50 ft. 1202794 Lifeline, 5901583 Flexible Counter-weight, 1220007 3 ft. Shock Absorbing Lanyard, 1003000 3 ft. Tie-Off Adaptor, 9511597 Carrying Bag
- 5000401 - 5000400 system except with 100 ft. 1202844 Lifeline and 9503806 Bag

With a full quality assurance program certified under ISO 9001, DBI/SALA supplies the industry with a quality range of safety products to provide added security. That's why we back each of our fall protection and rescue systems with the best training, tech assistance and customer service in the business. It makes life easier for you and safer for the workers up there.