

ECONOMICAL DEPENDABLE SAFE

With a Rebel Self Retracting Lifeline (SRL), you get an economical fall protection solution that won't compromise the safety or performance of your crew. Rebel continues to set performance standards beyond compliance, while providing a substantial value compared to competitive models.

- Improved Shock Pack Design (6' - 20' Units)
- Rugged, Lightweight Housing
- Recessed Labels To Increase Product Life
- Impact Indicator
- Swiveling Anchorage
- 3,600 Lb. Gate Capacity
- 420 Lb. Models Available (33' units and above)



3100432
REBEL 20 Ft. (6.1 m) SRL

20 ft. (6.1 m) of 1" (2.5 cm) polyester web with steel swiveling snap hook, swiveling anchorage and carabiner.



3590019
REBEL 15 Ft. (4.5 m) SRL

15 ft. (4.5 m) of 3/16" (5 mm) galvanized steel wire rope with steel swiveling snap hook, swiveling anchorage and carabiner.



3100425
REBEL 11 Ft. (3.3 m) SRL

11 ft. (3.3 m) of 1" (2.5 cm) polyester web with steel snap hook, swiveling anchorage and carabiner.



DOZENS OF WAYS TO STAY COMPLIANT WITHOUT COMPROMISE

		Web/Cable Length		6'	11'	15'	20'	33'	50'	66'	85'	100'
				(1.8 m)	(3.3 m)	(4.5 m)	(6 m)	(10 m)	(15 m)	(20 m)	(26 m)	(30 m)
Lifeline Material	Thermoplastic Housing											
	Aluminum Housing											
	Stackable											
	Impact Indicator											
	Swiveling Anchorage											
	Self Locking Snap Hook											
	Rebar Hook											
	Swiveling Hook											
	Leading Edge											
	100% Tie-Off											
	310 lb. (140 kg) Weight Capacity											
	420 lb. (190 kg) Weight Capacity											
Galv Cable				3590015	3590016	3590019						
						3590018						
							3590517	3590500	3590550	3590590	3590630	3590670
							3590514	3590510	3590560	3590600	3590640	3590680
							3590540					
SS Cable							3590504	3590501	3590551	3590591	3590631	3590671
							3590509	3590511	3590561	3590601	3590641	3590681
Web				3100403	3100425		3100431					
				3100404	3100426		3100432					
				3100405	3100427		3100433					
				3100412								
				3100413								
				3100414								
	Weight		Varies	Varies	Varies	Varies	13.5 lb. (6.1 kg)	17.3 lb. (7.8 kg)	22 lb. (10 kg)	28.6 lb. (13 kg)	29.5 lb. (13.4 kg)	
	Approximate depth		2" (5 cm)	3" (8 cm)	3" (8 cm)	4.6" (12 cm)	4.6" (12 cm)	4.6" (12 cm)	5.5" (14 cm)	5.5" (14 cm)	5.5" (14 cm)	
	Approximate width		3.5" (8.9 cm)	6" (15 cm)	6" (15 cm)	9.8" (24.9 cm)	9.8" (24.9 cm)	11" (28 cm)	12.8" (33 cm)	12.8" (33 cm)	12.8" (33 cm)	
	Approximate height*		19" (48 cm)	19" (48 cm)	29" (74 cm)	22.5" (57.1 cm)	22.5" (57.1 cm)	23.8" (61 cm)	25.7" (65 cm)	25.7" (65 cm)	25.7" (65 cm)	

*Anchor point to anchor point

Standards: Meets OSHA 1926.502, OSHA 1910.66, ANSI Z359.1, ANSI Z359.12, ANSI A10.32, CSA Z259.2.2 Type II



Capital Safety
 USA: 800 328 6146
www.capitalsafety.com info@capitalsafety.com

[@Capital_Safety](https://twitter.com/Capital_Safety) [Facebook.com/CapitalSafety](https://www.facebook.com/CapitalSafety)

FOR MORE INFORMATION VISIT US AT CAPITALSAFETY.COM