

FALL ARREST & LADDER SYSTEM – SETUP & SPECIFICATIONS

Each Freestanding Ladder System combines easy access to elevated work areas with 100% fall protection for up to two users from the ground up for the duration of the work being performed. System configurations include guardrails and the use of multiple SRLs on the system. These models are ANSI, OSHA and CE compliant.

Additional Fall Arrest & Ladder System Options:

- 8 in. (0.2m) Urethane Wheel Set
- Custom Paint Job
- Grounding Reel
- Low Profile Kit
- Tow Bar

Fixed height options:

- Manual height adjustment via winch assembly
- Multiple height adjustment ranges available
- All systems include a fall arrest bar for accessing ladder
- System includes heavy-duty leveling jacks



PLATFORM HEIGHT	SYSTEM TYPE	WHEELS	# OF USERS	PART #
10.75-15.5 FT. (3.3-4.7M)	PORTABLE LADDER	16 IN. (0.4M) PNEUMATIC	2	8517715
14.5-23 FT. (4.4-7.0M)	PORTABLE LADDER	16 IN. (0.4M) PNEUMATIC	2	8517717
18.25-31 FT. (5.6-9.4M)	PORTABLE LADDER	16 IN. (0.4M) PNEUMATIC	2	8517719